



**PUBLIC WORKS DEPARTMENT**  
Timm Borden, Director

CITY HALL  
10300 TORRE AVENUE ~ CUPERTINO, CA 95014-3266  
(408) 777-3354 ~ FAX (408) 777-3333

**ADDENDUM NO. 1**  
**2017 PAVEMENT MAINTENANCE PROJECT - PROJECT # 2017-104**  
**BID OPENING: November 1, 2016**  
**2:00 P.M.**

*ISSUED DATE: October 20, 2015*

**Engineer's Estimate - \$3,560,000.00**

The following revisions are hereby made to the above referenced project.

1. Replace current Document 00400 Bid Form with revised Document 00400 Bid Form attached to this addendum. Bid Item 43 has been added.
2. Replace current Document 00850 Technical Specification with revised Document 00850 Technical Specifications attached to this addendum. Section 8 "AC Dike" has been added.
3. Replace current Document 00864 Estimated Quantities with revised Document 00864 Estimated Quantities attached to this addendum. Five hundred linear feet of asphalt dike has been added on Upland Way.

All questions regarding this project must be transmitted in writing to Roger Lee, Assistant Director of Public Works. Fax number is 408-777-3333 and email address is [RogerL@cupertino.org](mailto:RogerL@cupertino.org).

Please indicate receipt of this addendum on the last page of the Proposal. Failure to do so may cause rejection of your bid.

APPROVED BY:

A handwritten signature in black ink, appearing to be "Timm Borden", is written over a horizontal line.

Timm Borden  
Director of Public Works

DOCUMENT 00400

**BID FORM**

To be submitted as part of Envelope "A" by the time and date specified in Document 00200 (Instructions to Bidders).

**TO THE HONORABLE CITY COUNCIL OF THE CITY OF CUPERTINO**

THIS BID IS SUBMITTED BY:

---

(Firm/Company Name)

**Re: PROJECT NUMBER 2017-104  
2017 PAVEMENT MAINTENANCE PROJECT**

1. The undersigned Bidder proposes and agrees, if this Bid is accepted, to enter into a contract with the City of Cupertino ("City") in the form included in the Contract Documents, Document 00520 (Contract), to perform and furnish all Work as specified or indicated in the Contract Documents for the Contract Sum and within the Contract Time indicated in this Bid and in accordance with all other terms and conditions of the Contract Documents. All portions of this Bid Form must be completed and signed before the bid is submitted. Failure to do so will result in the bid being rejected as non-responsive.
2. Bidder accepts all of the terms and conditions of the Contract Documents, Document 00100 (Advertisement for Bids), and Document 00200 (Instructions to Bidders), including, without limitation, those dealing with the disposition of Bid Security. This Bid will remain subject to acceptance for 90 Days after the day of Bid opening.
3. Bidder has visited the Site and performed all tasks, research, investigation, reviews, examinations, and analysis and given notices, regarding the Project and the Site, as set forth in Document 00520 (Contract), Article 5.
4. Bidder has given City prompt written notice of all conflicts, errors, ambiguities, or discrepancies that it has discovered in or among the Contract Documents and as-built drawings and actual conditions and the written resolution thereof through Addenda issued by City is acceptable to Contractor.
5. Subcontractors for work included in all Bid items, in accordance with the criteria in the Public Contract Code, are listed on the attached Document 00430 (Subcontractors List).
6. The undersigned Bidder understands that City reserves the right to reject this Bid.
7. If written notice of the acceptance of this Bid, hereinafter referred to as Notice of Award, is mailed or delivered to the undersigned Bidder within the time described in paragraph 2 of this Document 00400 or at any other time thereafter before it is withdrawn, the undersigned Bidder will execute and deliver the documents required by Document 00200 (Instructions to Bidders) within the times specified therein. These documents include, but are not limited to, Document 00520 (Contract), Document 00610 (Construction Performance Bond), and Document 00620 (Construction Labor and Material Payment Bond).
8. Notice of Award or request for additional information may be addressed to the undersigned Bidder at the address set forth below on the signature page.
10. The undersigned Bidder herewith encloses cash, a cashier's check, or certified check of or on a responsible bank in the United States, or a corporate surety bond furnished by a surety authorized to do a surety business in the State of California, in form specified in Document 00200 (Instructions to Bidders), in the amount of ten percent (10%) of the total of Bid and made payable to the "City of Cupertino".

11. The undersigned Bidder agrees to commence Work under the Contract Documents on the date established in Document 00700 (General Conditions) and to complete all work within the time specified in Document 00520 (Contract). The undersigned Bidder acknowledges that City has reserved the right to delay or modify the commencement date. The undersigned Bidder further acknowledges City has reserved the right to perform independent work at the Site, the extent of such work may not be determined until after the opening of the Bids, and that the undersigned Bidder will be required to cooperate with such other work in accordance with the requirements of the Contract Documents.
12. The undersigned Bidder agrees that, in accordance with Document 00700 (General Conditions), liquidated damages for failure to complete all Work in the Contract within the time specified in Document 00520 (Contract) shall be as set forth in Document 00520 (Contract).

## **NOTICE**

### *Required Contractor and Subcontractor Registration*

**1. Owner shall accept Bids only from Bidders that (along with all Subcontractors listed in Document 00430, Subcontractors List) are currently registered and qualified to perform public work pursuant to Labor Code Section 1725.5.**

**2. Subject to Labor Code Sections 1771.1(c) and (d), any Bid not complying with the preceding paragraph shall be returned and not considered; provided that if Bidder is a joint venture (Business & Professions Code Section 7029.1) or if federal funds are involved in the Contract (Labor Code Section 1771.1(a)), Owner may accept a non-complying Bid provided that Bidder and all listed Subcontractors are registered at the time of Contract award.**

**SCHEDULE OF BID PRICES****BASE BID ITEMS**

All Bid items, including lump sums and unit prices, must be filled in completely. Quote in figures only, unless words are specifically requested.

ITEM	DESCRIPTION	UNIT	EST. QNTY	UNIT COST	TOTAL
1	Traffic Control	LS	1		
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	5,075		
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	21,568		
4	Pavement Fabric	SY	177,673		
5	Keycut A	LF	92,514		
6	keycut B	LF	6,320		
7	Adjust Survey Monument Cover to Finish Grade	EA	174		
8	Replace Monument Box	EA	0		
9	Lower Manhole Covers Prior to Cold Planing	EA	29		
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold Planing	EA	16		
11	Adjust Manhole Covers to Finish Grade	EA	188		
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Grade	EA	31		
13	Install Blue RPM's @ Fire Hydrant	EA	42		
14	6" White Lines (Thermo)	LF	611		
15	12" White Hatch (Thermo)	LF	0		
16	12" White Crosswalk/Limit Line (Thermo)	LF	1,645		
17	12" Yellow Crosswalk (Thermo)	LF	100		
18	24" White (Thermo)	LF	0		
19	24" Yellow (Thermo)	LF	1,530		
20	Striping Detail # 10 (Markers)	LF	1,060		
21	Striping Detail # 22 (Thermo & Markers)	LF	2,100		
22	Striping Detail # 27B (Thermo)	LF	680		
23	Striping Detail 27B Modified (4'seg with 6' gap) (Thermo)	LF	100		
24	Striping Detail # 39 (Thermo)	LF	630		
25	Striping Detail # 39A (Thermo)	LF	300		
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	1		
27	"STOP" Legend (Pre-formed Thermo)	EA	37		
28	"SLOW" Legend (Pre-formed Thermo)	EA	4		
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	4		
30	"XING" Legend (Pre-formed Thermo)	EA	4		
31	"25" Legend (Pre-formed Thermo)	EA	11		
32	"YIELD" Legend (Pre-formed Thermo)	EA	0		

33	"BUMP" Legend (Pre-formed Thermo)	EA	14		
34	Green Bike Lane (Pre-formed Thermo)	SF	546		
35	Bike Rider Symbol (Pre-formed white on green)	EA	4		
36	Bike Rider Arrow (Pre-Formed white on green)	EA	4		
37	Bike Detection Symbol (Pre-formed white on green)	EA	1		
38	Arrow Type IV (Pre-formed Thermo)	EA	12		
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	12		
40	Replace Traffic Signal Loops	EA	3		
41	Remove/Install Speed Bump (City detail 17-1)	EA	2		
42	Remove/Install Speed Bump (City detail 17-A modified for 12' width)	EA	6		
43	6" AC DIKE	LF	500		

**TOTAL** \_\_\_\_\_

**Total Base Bid Price:** \_\_\_\_\_  
 (Words)

Unit Legend

- LS = Lump Sum
- EA = Each
- LF = Linear Feet
- TN = Ton or 2,000 Pounds
- SY = Square Yards
- SF = Square Foot

**ACKNOWLEDGEMENT OF RECEIPT OF ADDENDUMS**

Bidder hereby acknowledges receipt and examination of all Contract Documents and the following Addenda:

Addendum No.	Addendum Date

Bidder proposes and agrees to fully perform the Work within the time stated and in strict accordance with the Contract Documents for the sums of money listed in this Bid Form.

**NAME OF BIDDER:** \_\_\_\_\_

licensed in accordance with an act for the registration of Contractors, and with license number: \_\_\_\_\_

Expiration Date: \_\_\_\_\_.

\_\_\_\_\_  
Where incorporated, if applicable

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_  
Principals

I certify (or declare) under penalty of perjury under the laws of the State of California that the foregoing is true and correct.

\_\_\_\_\_  
Signature of Bidder

NOTE: If Bidder is a corporation, set forth the legal name of the corporation, state where incorporated, together with the signature of the officer or officers authorized to sign contracts on behalf of the corporation. If Bidder is a partnership, set forth the name of the firm together with the signature of the partner or partners authorized to sign contracts on behalf of the partnership.

Business Address:

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Officers authorized to sign contracts:

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\_\_\_\_\_  
Typed Full Name:

Telephone Number(s):

\_\_\_\_\_

Fax Number(s):

\_\_\_\_\_

E-Mail Address:

\_\_\_\_\_

END OF DOCUMENT

**DOCUMENT 00850****TECHNICAL SPECIFICATIONS**

## 1. TRAFFIC CONTROL (Bid Item Number 1)

## a. Item Requirement

Contractor shall furnish all necessary supervision, labor, materials, construction tools and equipment, supplies to complete traffic control at each location during the times immediately prior, during and after work.

## b. Scope

Construction area signs shall be furnished, installed, and removed when no longer required. The Contractor's attention is directed to Section 7-1.08, "Public Convenience", Section 7-1.09, "Public Safety", and Section 12, "Construction Area Traffic Control Devices", of the Caltrans Standard Specifications and Section 00820 Traffic Control Requirements of these specifications.

All traffic control devices shall conform to the latest "Manual of Traffic Control for Construction and Maintenance Work Zones" issued by Caltrans.

- (a) Advance construction warning signs shall be placed on all streets leading into the construction area before any construction is started.
- (b) Speed limit advisories may be placed along the main traffic lanes.
- (c) When detours or changes in traffic lanes are required, directional signs shall be placed at each end and along the roads.
- (d) Warning signs, caution signs, and end construction signs, shall be placed at each end of the work and along the route when conditions warrant their use.

**The Contractor shall submit a detailed traffic control plan for all work that requires lane closures at least 5 days prior to the lane closure. No lane closure will be allowed without prior approved traffic control plan specific to that location.**

The Contractor is responsible for proper placement and maintenance of all signs and barricades. Any additional signs, barricades, lights, etc., that may be required by the Engineer to ensure public safety shall be installed and maintained by the Contractor.

**Note: Traffic Controls – Qualified Individual:** Traffic controls through the construction zone shall be designed and maintained by a designated individual qualified in this responsibility. **The Contractor shall submit the traffic control plan and have an approved traffic control plan prior to commencing work. Traffic control shall be planned for each individual lane closure with detail layouts of all signage locations. For all other locations, Contractor shall provide traffic control plan indicating each**

**specific street(s) to be worked on a daily basis and warning signage to be placed on adjacent streets for warn public of work areas.**

If required in the traffic control plan, and always during one way traffic control, flagmen will be required to direct traffic during construction. The number and location of flagmen shall be sufficient to allow safe control and passage of traffic through the work zone. During the paving of intersections, two flagmen shall be posted at each intersection for the entire time between tack coat and finish rolling.

If a cross street needs to be temporarily closed when work is in progress through the intersection and the anticipated delay is more than five minutes, a detour sign shall be installed on the cross street and shall include the installation of advance signing displaying the anticipated delay time. The signing shall be reviewed by the Traffic Engineer.

Contractor shall supply **two (2)** programmable message boards per arterial / collector street a minimum of one week in advance of any work at designated locations as advanced information signs. The message shall be pre-approved by the Engineer prior to programming.

The term “Construction Area Signs” shall include all temporary signs required for the direction of public traffic through or around the work during construction. Such signs are shown in or referred to in the current MANUAL OF TRAFFIC CONTROLS – Warning signs, Lights and Devices for Use in Performance of Work Upon Highways, published by the State of California, Department of Transportation, hereinafter referred to as MANUAL OF TRAFFIC CONTROLS.

Restrictions on Closure of Traffic Lanes

The streets shall be open for use by public traffic on Saturday, Sunday, and any day designated by the City as a legal holiday; before 8 a.m. and after 5 p.m., Monday thru Friday, or any day preceding a designated legal holiday; and when construction operations are not actively in progress on working days. During daily construction operations, there may be certain peak traffic hours that would require the Contractor to alter the construction schedule in order to minimize the impact of the work on the public’s convenience.

The following provisions shall apply on the listed street segments:



<u>Street</u>	<u>Special Traffic Control Provision</u>
<u>Arterials:</u>	Lane closures are limited to one lane at a time . The roadway shall be open for two-way traffic at all times.
<u>Other Collectors:</u>	On four lane streets, one lane in each direction shall be maintained at all times. On two lane streets, flagmen shall be used to maintain traffic flow.
<u>Streets Near Schools:</u> See Attachment A	Work will be limited to days when school is out of session, (June 8, 2017 – August 11, 2017
<u>Residential:</u>	Traffic may be limited to only local traffic during the period between 8 a.m. and 5 p.m. Hauling of equipment and materials is prohibited within 500' of any school between the hours of 7:00 AM and 9:30 AM and 2:00 PM and 4:00 PM. Contractor is responsible for identifying locations of schools and planning haul route accordingly.

**Refer to “Attachment A” – Work Hour Restrictions for working hour requirements for each street or street category.**

Attention is directed to Sections 7-1.08, “Public Convenience,” 7-1.09, Public Safety,” and 12, “Construction Area Traffic Control Devices,” of the State Standards and to the Section entitled “Public Safety” and flagging for traffic control systems elsewhere in these technical specifications. Nothing in these technical specifications shall be construed as relieving the Contractor from his responsibility as provided in said Section 7-1.09.

A minimum of two (2) message boards shall be used at each work area located on a Collector or Arterial Street. The message shall be pre-approved by the Engineer prior to programming

Lane closures shall conform to the provisions in the section of these special provisions entitled “Traffic Control for Lane Closure.”

Personal vehicles of the Contractor’s employees shall not be parked on the traveled way or shoulders, including any section closed to public traffic.

The Contractor shall notify local authorities of his intent to begin work at least 7 calendar days before work is begun. The Contractor shall cooperate with local authorities relative to handling traffic through the area and shall make his own arrangements relative to keeping the working area clear of parked vehicles.

Whenever vehicles or equipment are parked on the shoulder within 6 feet of a traffic lane, the shoulder area shall be closed with fluorescent traffic cones or portable delineators placed on a taper in advance of the parked vehicles or equipment and along the edge of the pavement at 25-foot intervals to a point not less than 25 feet past the last vehicle or piece of equipment. A minimum of 9 cones or portable delineators shall be used for the taper. A C23 (Road Work Ahead) or C24 (Shoulder Work Ahead) sign shall be mounted on a telescoping flag tree with flags. The flag tree shall be placed where directed by Engineer.

In order to minimize the impact on local merchants, and residents, driveways shall not be blocked for any long periods of time. The Contractor shall maintain access to all driveways before and after road material is placed. The Contractor shall limit the time between the prep time placing and curing time of the asphalt material and cleanup so that vehicles may return the roadway to use.

The full width of the traveled way shall be open for use by public traffic on weekends, designated legal holidays, and when construction operations are not actively in progress.

Minor deviations from the requirements of this section concerning hours of work which do not significantly change the cost of the work may be permitted upon the written request of the Contractor if in the opinions of the Engineer public traffic will be better served and the work expedited. Such deviations shall not be adopted until the Engineer has indicated his written approval. All other modifications will be made by contract change orders.

A traffic control system shall consist of closing traffic lanes in accordance with the provisions of Section 12, "Construction Area Traffic Control Devices," of the State Standards, the provisions under "Maintaining Traffic" elsewhere in these technical specifications.

The provisions in this section will not relieve the Contractor from his responsibility to provide such additional devices or take such measures as may be necessary to comply with the provisions in Section 7-1.09, "Public Safety," of the State Standards.

If any component in the traffic control system is damaged, displaced, or ceases to operate or function as specified, from any cause, during the progress of work, the Contractor shall immediately repair said component to its original condition or replace said component and shall restore the component to its original location.

Lane closures are made for work periods only, at the end of each work period, all components of the traffic control system, except portable delineators placed along the traveled way, shall be removed from the traveled way, shoulder and auxiliary lanes.

### c. Measurement & Payment

The contract lump sum price paid for Traffic Control shall include full compensation for furnishing all labor including flagging costs, materials (including signs), tools, equipment and incidentals, and for doing all the work involved in placing, removing, storing, maintaining, moving to new locations, replacing and disposing of the components of the traffic control system and preparing required traffic control plans, as specified in the State Standards and these technical specifications, and as directed by the Engineer.

## 2. HOT MIX ASPHALT TYPE A(Bid Item Numbers 2- 3)

### a. Item Requirement

Work to be performed under this Section covers all labor, materials, tools, equipment, transportation, and incidentals necessary to construct HMA including leveling, overlay, pavement replacement, transitions and digouts.

All such work shall conform to the applicable provisions of the State of California, Department of Transportation, Standard Specifications (Caltrans) dated 2010; these Technical Specifications; and the plans and typical sections.

### b. Scope

All asphalt concrete materials shall be as specified in Section 39, "J Hot Mix Asphalt", of the Standard Specifications; these Technical Provisions; and the plans and typical sections.

#### Mix Types

Generally, the hot mix asphalt to be used will be as follows unless modified by the Engineer:

Base Courses: 3/4 inch, Type A HMA, for base courses greater than 2-1/2 inches (0.20 feet or 65 mm).

1/2 inch Type A HMA for base courses of 2-1/2 inches (0.20 feet or 65 mm) or less.

Leveling Courses: No. 4 , Type A HMA for leveling courses of 1 inch (0.06 feet or 19 mm) or less. 3/8 inch Type A HMA, for leveling courses greater than 1 inch (0.06 feet or 19 mm)-

Surface Courses: 1/2 inch, Type A HMA, for surface courses of 2-1/2 inches (0.20 feet or 65 mm) or less on residential minor collectors; surface courses less than 2 inches (0.17 feet or 50 mm) on collectors and arterials; and on all alleyways and parking lots.

3/4 inch Type A HMA for surface courses greater than 2 inches (0.17 feet or 50 mm) on collectors and arterials. At the Contractors option, 1/2- inch Type A HMA may be used for these courses.

#### Binder Type

The asphalt grade shall be PG 64-16 and shall conform to Subsection 92 of the Standard Specifications.

#### Tack Coat

Tack coat shall be utilized and will be emulsified asphalt Grade RS-1, RS-1h, SS-1, or SS-1h and shall conform to Section 94, 'Asphaltic Emulsions', of the Standard Specifications.

#### Contractor-Supplied Job Mix Formula (JMF)

The contractor will be required to furnish the Engineer with a JMF for each type of asphalt concrete to be used on the project. The JMF shall include a list of material sources and a Certificate of Compliance signed by the material supplier or his representative indicating that the materials to be incorporated in the work fulfill the requirements of these specifications. This submission will be provided fifteen calendar days or ten working days prior to the start of work. If requested, the contractor will also provide aggregate and binder samples or a plant produced mix sample for mix design verification. The mix designs shall be prepared by laboratories and personnel with current Caltrans or AASHTO certification.

The asphalt concrete mixtures shall conform to all of the provisions of the revised Section 39 of the Standard Specifications and to the following requirements:

For arterial and collector streets the asphalt concrete air void content shall be between 4% minimum and 5% maximum and the S-value shall be 37 or greater.

For residential streets and collectors the asphalt concrete air void content shall be between 3% minimum and 4.0% maximum and the S-value shall be 35 or greater.

As a minimum, the mix design shall indicate the percentage passing for each specified sieve, the percent of asphalt, the laboratory compacted unit weight, the theoretical unit weight (Rice Gravity), and the stability of the mix to be used for each asphalt concrete mixture to be incorporated on the project. The mix design, with allowable tolerance for a single test, shall be used for job control.

#### Delivery Tickets

Each delivery ticket shall include information on the material type, binder type, oil content, and the mix design number. Material delivered to the project without such annotations shall be subject to rejection.

### CONSTRUCTION

#### Surface Preparation

The work shall consist of preparing the existing street surfaces prior to the commencement of paving. Such work shall include removing raised pavement markers,

removing surface mounted concrete centerline dividers where applicable, removing thermoplastic traffic markings and legends, controlling nuisance water, sweeping, watering, and removing loose and broken asphalt concrete pavement and foreign material as specified in the Standard Specifications and these Technical Specifications, and as directed by the Engineer.

#### Prime Coat

No prime coat is required.

#### Tack Coat

Tack coat shall be applied to all existing asphalt concrete or Portland cement concrete surface to be paved over. The tack coat shall conform to the requirements in Section 39 of the Standard Specifications.

All vertical edges to be paved against shall be tack coated. These include, but are not limited to, curb faces, gutter lips, swale edges, cross gutter edges, and asphalt concrete edges. Vertical edges shall be tack coated by hand wand or manually by brush. The tack coat application shall not extend above the level of the finished surface by more than 1 inch. Gutter pans and curb faces not to be tack coated shall be protected by shields or other methods. An overspray beyond the one inch shall be removed by means approved by the Engineer.

Existing curb faces and driveways shall be protected against disfigurement from the asphalt. Residue of the material shall be removed from curb faces and driveways by sandblasting to the extent required by the Engineer.

The CONTRACTOR shall be responsible for cleaning tack coat tracked onto decorative concrete crosswalks and thermoplastic legends and crossbars within the project limits and along truck haul routes used by the CONTRACTOR or his SUBCONTRACTORS. All haul routes for the work shall be designated. The haul routes shall be inspected by the City and CONTRACTOR prior to initiating work to photographically establish the existing conditions. Within 10 calendar days of completion of final paving, the City and CONTRACTOR shall reinspect the haul routes to determine the extent and locations of required cleaning. Cleaning shall be performed within 10 calendar days after the City delivers a written copy of the locations of required cleaning. Failure to meet this schedule, whether to reinspect or to perform cleaning, shall subject the CONTRACTOR to a liquidated damage of \$100 per calendar day per locations

#### Cold Joints

All cold joints, both longitudinal and transverse, shall be heated with a torch immediately prior to paving. Cold joints include previous passes placed more than three hours prior. All cold joints shall be tack coated.

#### Leveling, Transitions, and Asphalt Concrete Fills

A leveling course of variable thickness shall be placed and compacted prior to placing the surface course at locations where directed by the Engineer. The leveling course will be

used to correct pavement irregularities such as rutting, variable cross slope, or variable longitudinal slope. Where two overlays of different thickness abut at a longitudinal joint, the Contractor shall add to the thinner section to match the thicker lift and provide a smooth transition and uniform cross-fall. Cold planing ridges or other rises in the pavement surface may be required by the Engineer. The Engineer will determine the exact limits and thickness of the leveling courses, asphalt concrete fills, and transitions.

### Layout

The contractor shall layout and mark the location of the edges of the paving passes of the surface course to match the new layout of the lane lines. The layout shall be made at least 24 hours prior to paving. The layout shall be approved by the Engineer prior to paving.

If the striping is to remain unchanged, the edges of the paving passes shall conform to existing lane edges.

In all cases where practical, each lane shall be paved in a single pass. In tapered transition areas, the shoulder areas shall be paved first, then the through lane shall be hotlapped immediately after the shoulder paving.

For paving which incorporates new quarterpoints or gradebreaks due to keycuts or other conditions, the contractor shall provide equipment capable of adjusting to the new surface profile at the appropriate locations. The profile adjustments shall be within twelve inches of the actual quarterpoint or gradebreak.

The contractor shall take sufficient measurements during laydown to assure that the full design asphalt concrete layer depth is provided at each quarterpoint, gradebreak, and transition. Failure to provide the design depth at these areas will result in rejection of the work. Correction of this rejected work will include milling out the new asphalt concrete from the road edge to the centerline or nearest inside lane line and repaving. The minimum length of the milled and corrected area shall be fifty feet.

### Asphalt Depth

Asphalt thicknesses for arterial dig outs are 9 inches, collector dig outs are 6 inches, residential dig outs are 4 inches, cold planed fills are 4 inches, residential overlays are 2 inches, residential leveling (followed by an overlay) are ½ inch and residential leveling (not followed by an overlay) are 1 inch.

### Asphalt Dig Out – Safety

Final lift shall be in place within 72 hours of removing asphalt dig outs. Once the pavement is removed in asphalt removal and replacement areas, the Contractor shall diligently prosecute the work so that the deep lift is in place within the same working day. At no time shall there be a drop off greater than 0.1' (one-tenth of a foot) in the pavement overnight. No unnecessary delays shall be tolerated. By way of ascertaining and fixing the amount of damages, and not by way of penalty,

the Contractor shall pay the City the sum of three hundred dollars (\$300) per calendar day, for each excavated area that remains incomplete beyond the two calendar (2) day limit. Day one starts upon the initial removal. All liquidated damages in this Contract are cumulative.

#### Tolerances

The finished asphalt concrete surface shall be flush with, to 1/4 inch (0.20 feet or 6 mm) above, the gutter lips. The finished pavement surface shall not be lower than the gutter lips. The completed paving shall meet the following thickness tolerances:

Digouts: +/- 0.04 feet (12.5 mm)

Leveling Courses: Average Depth +/- 0.02 feet (6 mm)

Surface Courses: Minimum Depth: 0.12 feet (50 mm), /Average Depth shall equal design depth. (Contractor shall be within 5% of computed tonnage using the product of the measured area, design depth and average compacted unit weight in place.

#### Rolling and Compaction

Compaction of all surface courses 0.15 feet (1=3/4 inches) and digouts shall comply with the Standard Process density requirements

For leveling courses under, breakdown rolling shall consist of a single pass of a 8 ton minimum steel wheel roller, three coverages with a pneumatic roller followed by a finishing coverage with a steel wheel roller. Pneumatic rollers shall weigh between 8 and 12 tons.

In lieu of the core testing indicated in the revised specifications referenced above, the following shall apply: The compaction shall be computed for each lot, with a maximum lot size of 500 tons. Each street segment of less than 500 tons shall be its own unique lot. Core density/nuclear gauge shall be done per CTM 375, 'Determining the In-Place Density and Relative Compaction of Asphalt Concrete Pavement'. The average asphalt concrete density of each lot shall be between 92.5% and 96.0% of Maximum Theoretical Density. Individual test sites shall be between 91.0% and 97.0% of Maximum Theoretical Density. Core/nuclear densities shall be taken at a rate of no fewer than one core per 50 tons of mix. If compaction fails by nuclear methods, then core density/nuclear gauge correlation and/or core densities shall be used to establish compaction.

When core density is used to determine compaction, cores that fall between 91.0% and 97.0% of Maximum Theoretical Density shall be paid for by the owner. Failing cores shall be paid for by the Contractor. If the core density testing produces both passing and failing cores, the cost will be prorated between the owner and Contractor.

Compaction failing to meet the above criteria shall be subject to the payment reductions indicated in Section 39-2.03, "Reduced Payment Factors for percent of Maximum Theoretical Density and the payment shall apply to each 500 ton lot: The deductions shall be based on the average of the lot and/or reductions for individual test locations.

#### c. Measurement & Payment

Payment for each bid item shall be by the ton and shall include full compensation for furnishing all labor, materials, tools, equipment, transportation, incidentals; and for doing all of the work involved in constructing asphalt concrete pavement, tack coat, complete as detailed and as specified in these Technical Specifications.

### 3. PAVEMENT FABRIC / PAVEMENT MAT (Bid Item Number 4)

#### a. Item Requirement

The work shall consist of providing and installing pavement fabric or pavement mat prior to final paving course. All such work shall conform to the applicable provisions of the State of California, Department of Transportation, Standard Specifications (Caltrans) dated 2010; these Technical Specifications; and the plans and typical sections

#### b. Scope

##### MATERIALS

##### Pavement Fabrics

Pavement fabrics approved for use are: Amoco 4598, Trevira 011/200, Mirafi Mirapave 500, Linq AOH, or equivalent as approved by the Engineer.

The tack coat shall be emulsified asphalt of grades RS1, RS2, SS1, or SS1h, conforming to Section 94, 'Asphaltic Emulsions', of the Standard Specifications. Tack coat for Pavement Fabrics shall be either PG64-10 or PG 70-10.

##### CONSTRUCTION

##### Preparation

The Contractor shall prepare the asphalt concrete surface by removing all extraneous materials including dirt, clay, soil, vegetation, weeds, and loose aggregate.

The surface shall be dry prior to, during, and after installation of tack coat and fabric. Wet fabric shall be dried prior to placement of asphalt concrete.

##### Tack Coat

Tack coat shall be between 300 and 375 degrees Fahrenheit when applied, and will be applied at a rate of 0.25 to 0.30 gallons per square yard as directed by the Engineer. Tack coat spills or drools from the spray truck shall be heated and removed. Excess tack coat shall be covered with No. 30 sand.

Tack coat shall be allowed to cool to 200 degrees Fahrenheit or less prior to the placement of fabric.



The tack coat for cold planed areas shall be double that of the existing pavement or leveling courses. The cold planed areas shall be tack coated first and then recoated when the entire pavement is tack coated.

#### Fabric Installation

Fabric laps shall be two minimum to four inches maximum. The fabric shall be installed a maximum of 12 inches from the curb or gutter lip. The Contractor shall either provide a combination of roll widths to meet this requirement or shall hand trim the fabric during installation.

In Cul de Sacs, the fabric shall be hand laid in the bulbs parallel to the centerline and trimmed to be no more than 12 inches from the gutter lip. For hand laid areas, the fabric shall be completed hand broomed to seat the fabric. If the fabric is not completely seated, the fabric shall be rolled with a pneumatic roller prior to paving. On returns at cross streets, the fabric shall be laid in the full return and trimmed such that it is within 12 inches of the curb and laps do not exceed 4 inches.

Where the fabric is placed over new pavement which extends the full width of the pavement, it shall lap over new asphalt concrete a minimum of twelve inches. This does not apply to digouts.

If the pavement configuration requires that the fabric be laid manually, the fabric shall be placed in increments of thirty feet or less.

Pavement fabric shall be placed with a minimum of wrinkles. If the gather wrinkle is 1/2 inch or more, cut the wrinkle and apply additional tack coat and sand blotter if necessary. The presence of more than a few wrinkles shall be cause for rejecting the fabric installation. Rejected areas of fabric shall be relaid and seated with a pneumatic roller without additional tack coat.

Installed fabric is to be protected from damage by trucks, the paving machine, and other construction equipment.

Small quantities of sand or asphalt concrete may be spread to protect the fabric during installation.

Payment shall be measured per square yard and as marked in the field by the Engineer. The fabric quantity shall be measured only the fabric covered area not including overlaps. Roll counts shall not be a basis of payment.

The contract unit cost shall be considered full compensation for furnishing all labor, materials, tools, equipment, transportation, and incidentals; and for performing all of the work involved as detailed in the Standard Specifications, these Technical Specifications, and typical sections. No additional compensation will be allowed therefore.

#### 4. ASPHALT KEYCUT (Bid Item Number 5-6)

a. Item Requirement

Contractor shall furnish all necessary supervision, labor, materials, construction tools and equipment to complete asphalt removal and proper disposal at locations specified by the Engineer.

b. Scope

Asphalt shall be keycut prior to AC overlay. Keycut type A shall consist of longitudinal wedge cut of 0.17' by 6' (minimum). Keycut type B shall consist of a traverse wedge cut of .17' by 12 feet (minimum). The locations to key cut include, but are not limited to, any which abut any permanent structures such as curbs, concrete curbs, sidewalks, driveways, concrete slabs, speed bumps and catch basins. All other utilities such as manholes and water valves shall be raised. Grinding shall be in conformance with Section 42-2 of the Standard Specifications. Any sections of asphalt that becomes loose after keycutting shall be removed and disposed of by the Contractor at the Contractor's expense.

Conform grinding will be necessary at the beginning and ending of each street section such that the final asphalt surface provides a smooth transition to the adjacent existing surface. Conform grinding shall be fifteen feet (15') wide.

Pavement key cut shall not be allowed more than 48 hours prior to schedule overlay operations without written authorization from the Engineer.

Cold milling/wedge cutting machines shall be operated so as not to produce fumes or smoke. They shall be capable of planning/milling/wedge cutting the pavement without requiring the use of a heating device to soften the pavement during, or prior to, the cutting operation.

The Contractor shall be responsible for maintaining all wedge cuts, using cutback or other methods to prevent tire and suspension damage to vehicles and to prevent hazards to bicyclists and pedestrians.

Wedge cutting at corners, returns and hard to get areas shall be done with special grinding equipment capable of grinding such areas. Wedge cutting or grinding may encounter existing paving fabric on previously overlaid streets. No additional payment will be made for this condition. The same method shall be used on all structures that area left above the traveled asphalt surface.

Key cuts shall include the removal of excess asphalt concrete materials or slurry seals on the surface of gutters, cross gutters or other concrete surface which abut the pavement surface. The asphalt concrete or slurry materials shall be removed by methods which do not damage, stain or chip the existing concrete surfaces. Heating with a torch and scraping with hand tools such as shovels is acceptable.

c. Measurement & Payment

Asphalt keycut shall be measured by the lineal foot and as marked in the field by the Engineer. No payment shall be made for materials removed outside of the limits marked by the Engineer. The contract unit prices paid for asphalt keycut shall include full compensation for furnishing all labor, material, equipment, tools, and all other incidentals necessary to perform the full scope of work as described above, for removal, legal disposal or as specified herein and as directed by the Engineer including the removal of excess materials from the gutter or other concrete surfaces.

5. ADJUST UTILITY IRON (Bid Item Numbers 7-12)

a. Item Requirement

This work shall consist of raising or adjusting existing utility facilities such as manholes, valve boxes, sewer clean-outs, monument boxes, and monitoring well covers to the finish grade of the resurfaced asphalt pavement.

Facilities located in areas to be cold planed or keycut shall be lowered first and then adjusted to finish grade after completion of the resurfacing work. At various locations a monument box and cover shall be installed at finish grade over any unprotected, existing monument in the paved roadway.

All such work shall conform to the applicable provisions of the State of California, Department of Transportation, Standard Specifications (Caltrans) dated 2010; these Technical Provisions; typical sections; and as directed by the Engineer.

b. Scope

CONSTRUCTION

Notification

Non-city owned utilities exist within the limits of construction and may be included in the quantity for adjusting utility covers to grade as part of this contract. If this work is included, the Contractor shall be responsible for contacting owners of non-city owned utilities seven (7) days prior to beginning the resurfacing work to inform them of the construction schedule. Non-city owned utilities may include, but not be limited to, San Jose Water Company, California Water Company, Cupertino Sanitary District, Sunnyvale Sanitary District, PG & E, and Pacific Bell.

Preparation

The Contractor shall properly locate and tie all existing facilities to be raised in advance of paving operations. Each facility is to have a minimum of two tie off points. A copy of all utility cover tie-down measurements for each utility cover on each street in the project shall be supplied to the City representative prior to the commencement of any resurfacing work.

#### Protection of Facilities

Prior to lowering operations, sanitary and storm systems shall be protected by plywood covers. Plywood covers shall be a minimum of ½” thick, cut to fit the inside of the manhole, and remain in the manhole until all work is complete. Other facilities are to commensurately be protected from falling debris.

Care shall be taken to keep frames and covers clean. The Contractor shall completely protect with heavy plastic or other suitable material all utility covers or other items which are visible on the surface and will be covered by his operations. This shall be completed prior to the start of operations and approved by the Engineer. Any materials that adhere to the frames and covers shall be removed.

#### Temporary Patching

On streets to be cold planed or keycut, all utility covers within the planing limit shall be lowered prior to milling.

Lowered utility lids shall be temporarily patched using a cold-patch asphaltic material. Patches shall be made to be flush with the adjacent pavement surface.

Contractor shall keep on hand sufficient patching material to continuously maintain all patches and correct any which shift or otherwise deteriorate prior to milling. Shifted or dislodged patches which constitute a drop of .10 feet or greater shall be repaired in the same day that the problem is brought to the Contractor’s attention.

#### Adjustment

Facilities damaged by the Contractor shall be replaced at the Contractor’s expense. Facilities (box and lid or frame and cover) found existing in a damaged condition, and reported to the Engineer before disturbing, shall be replaced by the Contractor with materials furnished by the Owner.

#### Tolerances

The concrete around adjusted facilities shall be left 1-1/2 inches lower than the adjacent pavement. The concrete surface shall be tack coated with 0.10 gallons per square yard and paved with 3/8 inch Type A HMA.. Immediately after placement, the surface shall be sand sealed. Excessive sand on the surface after sealing shall be removed by the Contractor, as directed by the City Engineer.

The surface of the adjusted facilities shall be true to the new pavement surface to within 1/8 inch deviation. This tolerance shall apply in a single direction only, either up or down. In addition, the adjusted facility shall not vary to the high tolerance on one side and the low tolerance on the other (i.e. the total aggregate tolerance on both sides shall be limited to the 1/8 inch variation). This variation shall apply to the adjacent patch paving around the facility as well, such that neither the paving nor facility vary by more than the stated tolerances.

### Schedule

All facilities shall be adjusted to finish grade within 72 hours after the placement of the final surface paving on each individual street segment. If several lifts of pavement are to be placed, the facilities shall be raised if the paving operation ceases for more than 72 hours.

### Survey Monuments

Where new survey monument boxes and covers are required, the Contractor shall perform the installation without disturbing the location of the monument. If the monument is disturbed the Contractor will be responsible for re-establishing it as a monument in accordance with State laws. The work for placement of the box and cover over an existing monument will include removal and replacement of the asphalt concrete around the monument.

### Monitoring Wells

Where monitoring wells are to be overlaid, the location of the wells shall be marked on the curbs. A site sketch shall be provided to the city indicating the location and distances on the monitoring wells relative to the curb markings five days prior to paving. If the monitoring wells have frames and covers, the frames and covers shall be adjusted as part of this work and paid for as a valve cover.

## c. Measurement & Payment

Lowering facilities shall be measured and paid for by each unit as designated in the contract Bid Schedule. Raising or adjusting facilities to finish grade shall be measured and paid for by each unit designated in the contract Bid Schedule. All quantities will be determined from actual counts. The unit costs shall govern regardless of the method used to make the adjustments.

The above contract unit costs shall be considered full compensation for furnishing all labor, materials, tools, equipment, transportation, and incidentals; and for performing all of the work involved as detailed in the Standard Specifications, these Technical Specifications, and the plans and typical sections. No additional compensation will be allowed.

Failure to adjust utility facilities within 72 hours after placement of the surface course shall result in at liquidated damage of \$250 per facility location per calendar day.

## 6. ASPHALT STRIPING / MESSAGES & MARKERS (Bid Item Numbers 13-39)

### a. Item Requirement

The Contractor shall furnish and apply traffic stripes, characters, arrows, pavement markers, and other delineations and markings. These shall be reapplied in the original pattern on all roads except as directed by the Traffic Engineer. See Attachment "B" for a list of striping revisions. Additional striping changes may be requested by the Traffic Engineer. Contractor shall install traffic striping and markers in accordance with Sections 84 and 85, 'Traffic Stripes and Pavement Markings' and 'Pavement Markers' and the most recent version of the California MUTCD.

All pavement legends and traffic striping shall be applied in thermoplastic unless otherwise noted.

Temporary pavement marking materials must be on hand prior to the covering or demolition of existing pavement markings.

### b. Scope

#### MATERIALS

##### Pavement Delineation- Thermoplastic

Thermoplastic material shall be extruded thermoplastic meeting the requirements of Section 84-2 and specifically Section 84-2.03B Extruded Thermoplastic or City approved equivalent. Placement shall be performed as directed by the manufacturer.

Legends and arrows shall be preformed, thermoplastic pavement markings and shall be Ennis Flint Premark or a City approved equivalent except bid item # 47 which is to be paint. Placement shall be performed as directed by the manufacturer.

Paint for pavement markings shall be single coat and beaded, conforming to Caltrans Standard Specification Section 84.

All stencils and templates shall be identical with those currently used by the City of Cupertino.

#### Pavement Delineation- Pavement Markers

Raised and reflective pavement markers shall comply with Section 85 of the Standard Specifications. The specific type to be used shall be consistent with the type generally in use within the local jurisdiction unless directed otherwise by the Engineer.

#### Colored Bike Lane Surface Treatment

The colored bike lane surface treatment shall be high friction, non-slip, approved Caltrans green colored, fast back to traffic (within 2 hours of application), and durable. The surface treatment shall be Ennis-Flint's MMA Bike Lane treatment or a City approved equivalent. Contractor shall submit for approval a complete product specification and application process. Surface preparation, material storage, installation, masking, application shall be performed as required by the manufacturer's specifications.

The Contractor shall notify and coordinate with the City and with the schools and commercial establishments whose driveways will be affected by the installation of green bike lanes. The work in front of driveways shall be phased so that at least one directional traffic lane will be open for ingress and egress to the establishments. Newly installed green lanes shall be protected from traffic and damage until it is cured 100%, which will be a hardened solid state, before traffic is permitted. Masking and application of material shall be done with care to prevent overspill to adjacent striping, asphalt, or concrete structures. The Contractor will be responsible for removing material that has tracked and spilled on adjacent surfaces to the satisfaction of the Public Works Director.

The green bike lane surface treatment shall be light green color that meets FHWA specifications.

#### Preformed Thermoplastic Green Bike Lane including bike symbols, legends and arrows.

Green bike lanes shall be preformed thermoplastic pavement markings and shall be Premark Skid/Slip Resistant (90 mil) or a City approved equivalent. Bike symbols, legends, and arrows within green bike lanes and shall be Premark ViziGrip (90 mil) or a City approved equivalent. Placement shall be performed as required by the manufacturer's specifications.

Bike symbols, legends, and arrows in green bike lanes must be factory assembled with the green marking sheet and interconnected so that in the field it is unnecessary to assemble the individual pieces within a material segment.

The green bike lanes shall be pre-formed thermoplastic pavement marking sheets utilizing light green color that meets FHWA specifications for color.

A sealer specified by the manufacturer must be applied to the substrate asphalt and concrete to ensure proper adhesion.

Preformed green marking sheets shall be installed first before the 6" white liquid thermoplastic bicycle lane line. Pre-formed sheets shall be laid out and applied so that edges of adjacent sheets fit snugly together, the pattern of the marking aligns properly from sheet to sheet, and to prevent overlap of adjacent sheets.

First time applicators shall contact the pre-formed thermoplastic pavement marking supplier for product support and on-site training.

## CONSTRUCTION

All construction shall conform to the respective provisions of the Standard Specifications, manufacturer's installation requirements, and these Technical Specifications.

### Existing Striping and Markings

In areas adjacent to the pavement resurfacing or striping enhancements, where existing striping must be changed to conform to a revised striping pattern, conflicting striping shall be removed by sand blasting, grinding, or other methods as specified in the Standard Specifications or by the Engineer.

The Contractor shall replace all striping which has been damaged or obliterated by or during the work. This may include striping replacement completely across the street even in the event that the Contractor's work may not extend that far. Both lines of each crosswalk shall be completely repainted even if only a portion of a line has been obliterated.

### Layout for Temporary and Permanent Striping

The alignment and layout of traffic stripes shall conform to the Standard Specifications.

The Contractor shall perform all tie downs, layout, alignment, and spotting. Contractor shall submit a plan documenting location, dimensions, and Caltrans Standard Detail reference number or other applicable detail for all existing pavement striping, markings, markers and legends. The plan shall contain



sufficient detail for installation of new thermoplastic and markers. The plans shall be submitted prior to the pre-construction meeting and shall be approved by the Engineer prior to the issuance of Notice to Proceed. The Engineer or his/her designee shall review and approve striping layout prior to final striping.

The Contractor shall physically tie down the location of the beginning and ending of each paint or thermoplastic marking type in the adjacent curb top. The marking location shall not exceed fifty square inches each. Any locations exceeding this limit shall be removed by the Contractor prior to acceptance of the work. The Contractor shall contact the City Traffic Division for review of tie downs.

The Contractor shall be responsible for accurately referencing out and replacing the lines and positions of all traffic lines, directional lines, arrows, and other markings in accordance with either prior existing striping/message layout or by revised striping plans provided by the Engineer by cat tracking with painted marks. This shall occur no later than two hours after the final surface course paving operation.

Cat tracking shall consist of stretching a rope on a straight line between control points on tangent alignment and on a true arc through control points on curved alignment and placing spots of paint along the rope. Temporary tab markers shall be placed not more than twelve feet apart on curves nor more than twenty-four feet apart on straight segments.

Temporary tab markers shall be the same color as the traffic stripe that they are replacing, shall measure two inches tall by 3-1/2 inches wide, and have a reflective lens across the width of the marker.

Application of cat tracking and/or placement of temporary tab markers are to occur immediately upon completion of final compaction rolling and prior to opening asphalt areas to traffic. All crosswalks, stop bars and directional arrows, both yellow and white in color, shall be placed immediately upon completion of final compaction rolling and prior to opening asphalt areas to traffic. Cat tracking shall be complete and ready for City review by the sixth calendar day following paving. Failure to comply with these requirements shall result in a liquidated damage of \$500 per day for each street that has not received temporary installation of the tab markers, traffic striping, and other markings or completion of cat tracking. All liquidated damages in this Contract are cumulative.

Prior to application of permanent striping and markers, the Contractor shall call for review and approval of the proposed striping by the Engineer or his/her designee. The City shall have the right to make changes in the location and alignment of line stripes. Striping and traffic markings shall not be applied until approval is granted by the Engineer or his/her designee. The Contractor shall allow a minimum of seven working days for review of the layout by the City.

### Crosswalks

In some instances, portions of new crosswalks will extend beyond limit of pavement rehabilitation work. In these instances, the existing 12 inch wide lines outside the paving limit shall be removed by grinding or sandblasting prior to placing new crosswalk striping.

At various locations in the project, crosswalks shall be consist of a series of ten (10) foot width by two (2) foot length bars, with no perpendicular lines at the crosswalk sides, as shown in the 'Miscellaneous Details & City Standard Details' of the Contract Documents.

### Schedule

Raised pavement markers (RPM's) shall be placed to replace existing RPM's or as designated by City provided striping plans. When utilizing hot melt bituminous adhesive, RPM's shall be placed after the surface has been open to traffic for at least seven days. When utilizing epoxy adhesive, RPM's shall be placed after the surface has been open to traffic for at least fourteen days. Regardless of which adhesive is utilized, the RPM's shall not be placed more than twenty-one days after paving or surfacing.

Thermoplastic materials shall be placed to replace existing thermoplastic materials or as designated by City provided striping plans. Permanent traffic striping and markings including legends and arrows shall be placed between eight (8) and twelve (12) days after paving or surfacing, unless otherwise directed by the Engineer. All permanent striping shall be complete in place by the 22<sup>nd</sup> day after completion of resurfacing work. All permanent striping on streets near schools shall be installed prior to August 11, 2016. See Attachment A.

### Reflective and Raised Pavement Markers

Installation of both reflective and raised pavement markers shall conform to the provisions of Section 85 of the Standard Specifications. Pavement markers shall be placed in the same pattern and locations as they were previously, except as specified by the Engineer.

Reflective Pavement Markers at fire hydrants shall consist of placing a single blue marker on the new pavement surface. Location of the new marker shall be six (6) inches off of the lane striping nearest to and in line with the existing fire hydrant.

### Pavement Delineation- Thermoplastic

Pavement temperature shall be measured at the beginning of the shift on each working day and this information shall be provided to the Traffic Engineer.

No primer or thermoplastic shall be installed within forty-eight hours from the last measurable rain report as provided by the City.

Thermoplastic traffic striping, legends, and arrows shall conform to the provisions of Section 84-of the Standard Specifications and these Technical Provisions.

c. Measurement & Payment

Payment for traffic striping layout and placement of temporary lane markers will be included in the unit price bid for each striping detail as identified in the Bid Schedule and no additional compensation will be allowed therefore.

Measurement and payment for pavement striping, characters, arrows, pavement markers, raised pavement markers, and reflective pavement markers shall be paid on a unit cost basis as identified in the Bid Schedule.

Payment for any striping removal as identified herein shall be included in the unit price for the related striping item and no additional compensation will be allowed therefore.

The above contract unit costs shall be considered full compensation for furnishing all labor, materials, tools, equipment, transportation, and incidentals; and for performing all of the work involved as detailed in the Standard Specifications, these Technical Specifications, and the plans and typical sections. No additional compensation will be allowed therefore.

Failure to comply with these requirements shall result in a liquidated damage of \$150 per calendar day for each street that has not received permanent installation of the required raised pavement markers, traffic striping, and markings. All liquidated damages in this Contract are cumulative.

8. TRAFFIC SIGNAL LOOPS (Bid Item Number 40)

a. Item Requirement

Work to be performed under this Section covers all labor, materials, tools, equipment, transportation, and incidentals necessary to replace existing loop detectors at various street intersections. It is anticipated that all the existing loop detectors at the intersections will be damaged by the proposed pavement cold planing.

b. Scope

All replaced signal loops shall be Standard 6'x 6' rectangular loops as shown on plans and details unless specifically called out otherwise. Any changes to loop type, placement pattern, or installation may be performed only as allowed by the Engineer.

All such work shall conform to the details and provisions of the State of California, Department of Transportation's Standard Plans and Section 86, "Electrical Systems," of the Standard Specifications and these Technical Provisions, except that Subsection 86-8, "Payment," is modified herein.

### Intersection Locations

All left turn lane and through lane detector loops, including advance lane loops, shall be replaced to their existing locations, or as shown in plans provided by the City and to the details provided in these contract documents.

The proposed locations of the replaced signal loops detectors shall be marked in the field and approved by the Engineer prior to installation.

Maintaining the traffic signals during construction shall be a part of this work. The maximum time between disconnecting loops in operation until replacement shall be 14 working days. Failure to meet this schedule will cause the work to be performed by City forces and the Contractor backcharged for the work.

### Construction

All traffic loops shall be replaced after approval of cat tracking and prior to final striping.

Prior to initiating any work on the signal loops, the Contractor shall mark in the field location of new loops according to the plans and details. The City Traffic Division shall be contacted to review locations as marked by contractor. Loop installation operations shall commence only after approval is granted by Traffic Engineer.

Advance warning loops shall be installed 200 feet from limit line, as outlined in Table 9-1 'Suggested Detector Setbacks from Limitline' in the State Traffic Manual.

### Pull Boxes

Where the sump of an existing pull box is disturbed by the Contractor's operations, the sump shall be reconstructed and, if the sump was grouted, the old grout shall be removed and new grout placed.

## Detectors

Loop wire shall be Type II.

In Lieu of the requirements in the fourth paragraph of Section 86-5.01A(5), "Installation of Details," of the State Standard Specifications, slots in asphalt concrete pavement shall be filled as follows:

After conductors are installed in the slots cut in the pavement, paint binder shall be applied to all vertical surfaces of slots in accordance with the provisions in Section 94, "Asphaltic Emulsions," of the State Standard Specifications. The slots shall then be filled with asphaltic concrete sealants using hot melt loop sealant.

Temperature of sealant material during installation shall be above 70 degrees F. Air temperatures during installation shall be above 50 degrees F. Hot melt sealant placed in the slots shall be compacted by use of an 8-inch diameter by 1/8-inch thick steel hand roller or other tool approved by the Engineer. Compacted sealant shall be flush with the pavement surface. Minimum conductor coverage shall be 5/8 inch. Excess sealant remaining after rolling shall not be reused. Traffic may be released immediately over compacted material.

The Contractor shall test all detectors with a motor-driven cycle, as defined in the California Vehicles Code, that is licensed for street use by the Department of Motor Vehicles of the State of California. The unladen weight of the vehicle shall not exceed 220 pounds and the engine displacement shall not exceed 100 cubic centimeters. Special features, components or vehicles designed to activate the detector will not be permitted. The Contractor shall provide an operator who shall drive the motor-driven cycle through the response or detection area of the detector at not less than 3 miles per hour nor more than 7 miles per hour.

Detectors will be disconnected or connected by the Contractor. The Contractor shall notify the Engineer 24 hours prior to any detector being disconnected or connected. Timing adjustments shall be made by City traffic personnel.

Traffic signal loops damaged due to grinding, cold planing, digouts, paving or any other related construction shall be replaced within 2 weeks following the damage. Failure to comply with these requirements shall result in a liquidated damage of \$100 per day for each traffic signal loop not replaced with 2 weeks following the damage. All liquidated damages in this Contract are cumulative.

c. Measurement and Payment

The measurement and payment for replacing loop detectors, complete in place and operable, will be made at the unit bid price for each loop as listed in the bid schedule.

The unit price and payment shall include full compensation for furnishing all labor, materials, tools, equipment, transportation and incidentals, and for doing all the work involved in replacing the loop detectors, complete, as specified in these Technical Specifications.

7. SPEED BUMPS

Remove existing speed bumps prior paving. Install new speed bumps at existing location per City Standard detail 1-17A. The profile of new speed bumps shall match existing. On Hyannisport Dr and Kentwood Ave, new speed bumps will be construction per detail 1-17A, modified such that the width of section B-B equals 12 feet, eliminating the 10 foot flat section. New speed bumps shall be installed a minimum of 5 calendar days and a maximum of 10 calendar days following final paving.

8. 6" AC Dike (Bid Item 43)

a. Item Requirement –

The contractor shall furnish and install Type D Asphalt Dike in accordance with Caltrans Standard Detail A87B and section 39 of the State Standard Specifications (latest edition).

b. Payment

Payment shall be per lineal foot.

2017 Pavement Maintenance Project												
Engineer's Estimate - \$3,560,000.00												
		AREA #	4	7	7	9	9	9	9	9	9	9
Estimated Quantities			OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY
BID ITEM NO.	BID ITEM	UNIT	Creekline Dr (November to End)	Rainbow Dr (Villa Maria to End)	Upland (Wooley Way to End)	Candlelight Way (Crestline to Shadwohill)	Cleo (Gardenside to End)	Gardenside Ln (Rainbow to Kingsbury)	Kingsbury Ct	Kingsbury Pl (Candlelight to Scotland)	Lockford Ct (Scotland to End)	Shadowhill Ln (Stelling to Candlelight)
			AREA	41936	34681	51450	26865	7088	31925	5030	32834	14483
1	Traffic Control	LS									---	---
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	126	104	154	81	21	96	15	99	43	128
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	535	442	656	343	90	407	64	419	185	544
4	Pavement Fabric	SY	4,404	3,626	5,388	2,826	741	3,355	537	3,459	1,525	4,462
5	Keycut A	LF	2300	2044	2960	1430	420	1730	200	1700	760	2474
6	keycut B	LF	120	130	120	335	50	70	70	80	65	130
7	Adjust Survey Monument Cover to Finish Grade	EA	7	11	5	5	0	7	1	5	3	2
8	Replace Monument Box	EA	0	0	0	0	0	0	0	0	0	0
9	Lower Manhole Covers Prior to Cold Planing	EA	1	13	1	0	0	2	0	1	0	0
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold	EA	3	0	0	5	0	1	0	1	0	0
11	Adjust Manhole Covers to Finish Grade	EA	11	19	4	8	0	6	1	10	2	2
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Gra	EA	3	0	0	5	0	3	0	3	1	0
13	Install Blue RPM's @ Fire Hydrant	EA	2	0	2	2	0	1	0	2	1	0
14	6" White Lines (Thermo)	LF	0	2	0	0	0	0	0	0	0	0
15	12" White Hatch (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
16	12" White Crosswalk/Limit Line (Thermo)	LF	0	0	0	0	30	30	0	0	0	25
17	12" Yellow Crosswalk (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
18	24" White (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
19	24" Yellow (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
20	Striping Detail # 10 (Markers)	LF	0	0	0	0	0	0	0	0	0	0
21	Striping Detail # 22 (Thermo & Markers)	LF	0	0	0	0	0	0	0	0	0	0
22	Striping Detail # 27B (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
23	Striping Detail 27B Modified 4'seg with 6' gap) thermo	LF	0	0	0	0	0	0	0	0	0	0
24	Striping Detail # 39 (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
25	Striping Detail # 39A (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	0	0	0	0	0	0	0	0	0	0
27	"STOP" Legend (Pre-formed Thermo)	EA	0	0	0	0	1	1	0	0	0	1
28	"SLOW" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
30	"XING" Legned (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
31	"25" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	1	0	0	0	0
32	"YIELD" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
33	"BUMP" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
34	Green Bike Lane (Pre-formed Thermo)	SF	0	0	0	0	0	0	0	0	0	0
35	Bike Rider Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
36	Bike Rider Arrow (Pre-Formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
37	Bike Detection Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
38	Arrow Type IV (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	0	0	0	0	0	0	0	0	0	0
40	Replace Traffic Signal Loops	EA	0	0	0	0	0	0	0	0	0	0
41	Remove/Install Speed Bump (City detail 17-A)	EA	0	0	0	0	0	0	0	0	0	0
42	Remove/Install Speed Bump (Modified City detail 17-A 12' section)	EA	0	0	0	0	0	0	0	0	0	0
43	6" AC Dike	LF	0	0	500	0	0	0	0	0	0	0

2017 Pavement Maintenance Project												
Engineer's Estimate - \$3,560,000.00												
		AREA #	9	10	11	11	11	11	11	15	15	15
Estimated Quantities			OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY
BID ITEM NO.	BID ITEM	UNIT	Squirewood Way (Scotland to Stelling)	La Paloma (Santa Teresa to Columbus)	Edward Way (Bubb to Ronald)	Fort Baker Dr (Presidio to Hyannisport)	Hyannisport Dr (Linda Vista to Bubb)	Maria Rosa Way (Rosario to Columbus)	Ronald Way (Edward to Rosario)	Kentwood Ave (600' W/O De Anza to Tiptoe)	Stanford Pl (Kentwood to Annette)	Steeplechase (Rollingdell to Kentwood)
			AREA	28543	35602	38759	15863	91212	14834	6663	56882	34628
1	Traffic Control	LS				---		---				---
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	86	107	116	48	274	45	20	171	104	74
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	364	454	494	202	1,163	189	85	725	442	315
4	Pavement Fabric	SY	3,003	3,750	4,086	1,656	9,582	1,585	701	5,825	3,621	2,593
5	Keycut A	LF	1520	1854	1988	956	4976	570	350	4460	2040	1400
6	keycut B	LF	110	140	70	45	300	80	40	210	0	0
7	Adjust Survey Monument Cover to Finish Grade	EA	2	4	1	0	10	1	0	5	2	4
8	Replace Monument Box	EA	0	0	0	0	0	0	0	0	0	0
9	Lower Manhole Covers Prior to Cold Planing	EA	2	0	0	0	3	0	0	2	0	0
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold	EA	0	0	1	0	0	0	0	0	0	0
11	Adjust Manhole Covers to Finish Grade	EA	6	2	2	0	11	0	0	9	2	0
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Gra	EA	1	0	1	0	0	0	0	2	0	0
13	Install Blue RPM's @ Fire Hydrant	EA	1	0	0	0	3	1	0	4	1	1
14	6" White Lines (Thermo)	LF	0	0	0	0	0	0	0	160	0	0
15	12" White Hatch (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
16	12" White Crosswalk/Limit Line (Thermo)	LF	30	30	25	25	180	0	0	0	0	0
17	12" Yellow Crosswalk (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
18	24" White (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
19	24" Yellow (Thermo)	LF	0	0	110	110	350	0	0	0	0	0
20	Striping Detail # 10 (Markers)	LF	0	0	0	0	1060	0	0	0	0	0
21	Striping Detail # 22 (Thermo & Markers)	LF	0	0	0	70	1350	0	0	290	0	0
22	Striping Detail # 27B (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
23	Striping Detail 27B Modified 4'seg with 6' gap) thermo	LF	0	0	0	0	0	0	0	0	0	0
24	Striping Detail # 39 (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
25	Striping Detail # 39A (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	0	0	0	0	1	0	0	0	0	0
27	"STOP" Legend (Pre-formed Thermo)	EA	1	1	0	1	5	1	0	0	0	0
28	"SLOW" Legend (Pre-formed Thermo)	EA	0	0	0	1	0	0	0	0	0	0
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	0	0	0	1	0	0	0	0	0	0
30	"XING" Legend (Pre-formed Thermo)	EA	0	0	0	1	0	0	0	0	0	0
31	"25" Legend (Pre-formed Thermo)	EA	1	0	0	1	1	0	0	0	0	0
32	"YIELD" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
33	"BUMP" Legend (Pre-formed Thermo)	EA	0	0	0	0	8	0	0	4	0	0
34	Green Bike Lane (Pre-formed Thermo)	SF	0	0	0	0	0	0	0	0	0	0
35	Bike Rider Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
36	Bike Rider Arrow (Pre-Formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
37	Bike Detection Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
38	Arrow Type IV (Pre-formed Thermo)	EA	0	0	0	0	1	0	0	0	0	0
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	0	0	0	0	0	0	0	0	0	0
40	Replace Traffic Signal Loops	EA	0	0	0	0	0	0	0	0	0	0
41	Remove/Install Speed Bump (City detail 17-A)	EA	0	0	0	0	0	0	0	0	0	0
42	Remove/Install Speed Bump (Modified City detail 17-A 12' section)	EA	0	0	0	0	4	0	0	2	0	0
43	6" AC Dike	LF	0	0	0	0	0	0	0	0	0	0



2017 Pavement Maintenance Project												
Engineer's Estimate - \$3,560,000.00												
		AREA #	16	16	18	18	19	20	20	20	21	21
Estimated Quantities			OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	Overlay	OVERLAY
BID ITEM NO.	BID ITEM	UNIT	Terry Way (Rodriges to End)	Western Dr (Rodrigues to Scofield)	Silverado Ave (Whitney to De Anza)	Suisun Dr (Blaney to Farallone)	Rampart Ave (E Estates to Glenview)	Deeprise (Price to End)	Mello PI (Price to End)	Price Ave (Blaney to Portal)	Calle De Barcelona (Finch to Miller)	Corte De Madrid (Calle De Barcelona to End)
		AREA	26265	29545	36605	41531	24440	5845	14837	35344	22893	6982
1	Traffic Control	LS	---	---					---	---		
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	79	89	110	125	73	18	45	106	69	21
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	335	377	467	530	312	75	189	451	292	89
4	Pavement Fabric	SY	2,782	3,134	3,828	4,370	2,556	597	1,561	3,719	2,378	734
5	Keycut A	LF	1230	1340	2154	2200	1440	472	790	1870	1490	376
6	keycut B	LF	170	140	120	120	120	0	0	120	120	40
7	Adjust Survey Monument Cover to Finish Grade	EA	2	3	0	1	0	1	3	0	2	1
8	Replace Monument Box	EA	0	0	0	0	0	0	0	0	0	0
9	Lower Manhole Covers Prior to Cold Planing	EA	0	0	0	0	0	0	0	0	0	0
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold	EA	0	0	0	0	0	0	0	0	3	0
11	Adjust Manhole Covers to Finish Grade	EA	0	3	0	5	2	1	4	7	2	1
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Gra	EA	0	0	0	0	0	0	0	0	3	1
13	Install Blue RPM's @ Fire Hydrant	EA	1	0	2	2	1	1	0	0	2	0
14	6" White Lines (Thermo)	LF	0	0	0	0	0	0	0	120	0	0
15	12" White Hatch (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
16	12" White Crosswalk/Limit Line (Thermo)	LF	0	60	110	30	125	30	30	150	180	0
17	12" Yellow Crosswalk (Thermo)	LF	0	100	0	0	0	0	0	0	0	0
18	24" White (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
19	24" Yellow (Thermo)	LF	0	0	0	110	0	0	0	0	80	0
20	Striping Detail # 10 (Markers)	LF	0	0	0	0	0	0	0	0	0	0
21	Striping Detail # 22 (Thermo & Markers)	LF	300	60	0	30	0	0	0	0	0	0
22	Striping Detail # 27B (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
23	Striping Detail 27B Modified 4'seg with 6' gap) thermo	LF	0	0	0	0	0	0	0	0	0	0
24	Striping Detail # 39 (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
25	Striping Detail # 39A (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	0	0	0	0	0	0	0	0	0	0
27	"STOP" Legend (Pre-formed Thermo)	EA	0	2	1	1	1	1	1	0	0	0
28	"SLOW" Legend (Pre-formed Thermo)	EA	0	0	0	1	0	0	0	0	0	0
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	0	0	0	1	0	0	0	0	0	0
30	"XING" Legned (Pre-formed Thermo)	EA	0	0	0	1	0	0	0	0	0	0
31	"25" Legend (Pre-formed Thermo)	EA	0	0	0	1	0	0	0	1	0	0
32	"YIELD" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
33	"BUMP" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	2	0	0
34	Green Bike Lane (Pre-formed Thermo)	SF	0	0	0	0	0	0	0	0	0	0
35	Bike Rider Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
36	Bike Rider Arrow (Pre-Formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
37	Bike Detection Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
38	Arrow Type IV (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	0	0	0	0	0	0	0	0	0	0
40	Replace Traffic Signal Loops	EA	0	0	0	0	0	0	0	0	3	0
41	Remove/Install Speed Bump (City detail 17-A)	EA	0	0	0	0	0	0	0	2	0	0
42	Remove/Install Speed Bump (Modified City detail 17-A 12' section)	EA	0	0	0	0	0	0	0	0	0	0
43	6" AC Dike	LF	0	0	0	0	0	0	0	0	0	0

2017 Pavement Maintenance Project												
Engineer's Estimate - \$3,560,000.00												
		AREA #	21	21	22	22	22	22	22	22	22	22
Estimated Quantities			OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY
BID ITEM NO.	BID ITEM	UNIT	Corte De Seville (Calle De Barcelona to End	Finch (Phil to Stevens Creek)	Crabtree Ln (Johnson to Sterling)	Culbertson Dr (Meiggs to Barnhart)	Johnson Ave (Loree to Barnhart)	Menhart Ln (Moretti to Calvert)	Moretti Dr (Loree to Barnhart)	Newsom Ave (Johnson to Wunderlich)	Tilson Ave (Tantau to Stern)	Wunderlich Dr (Tilson to Menhart)
		AREA	7643	109,412	15145	46162	59349	51076	46323	45275	39415	36,936
1	Traffic Control	LS			---	---	---	---	---	---	---	---
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	23	328	45	138	178	153	139	136	118	111
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	97	1,395	193	589	757	651	591	577	503	471
4	Pavement Fabric	SY	802	11,624	1,587	4,854	6,226	5,375	4,869	4,739	4,155	3,888
5	Keycut A	LF	426	4800	866	2480	3314	2700	2504	2628	2018	1940
6	keycut B	LF	40	225	130	240	80	210	160	90	200	100
7	Adjust Survey Monument Cover to Finish Grade	EA	1	0	2	6	4	4	3	3	4	0
8	Replace Monument Box	EA	0	0	0	0	0	0	0	0	0	0
9	Lower Manhole Covers Prior to Cold Planing	EA	0	0	0	0	0	0	0	0	0	0
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold	EA	0	0	0	0	0	0	0	0	0	0
11	Adjust Manhole Covers to Finish Grade	EA	1	0	1	2	4	3	3	2	3	1
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Gra	EA	1	0	0	0	0	0	0	0	0	0
13	Install Blue RPM's @ Fire Hydrant	EA	0	0	0	1	3	2	0	0	0	0
14	6" White Lines (Thermo)	LF	0	329	0	0	0	0	0	0	0	0
15	12" White Hatch (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
16	12" White Crosswalk/Limit Line (Thermo)	LF	0	0	60	25	0	50	40	0	140	25
17	12" Yellow Crosswalk (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
18	24" White (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
19	24" Yellow (Thermo)	LF	0	770	0	0	0	0	0	0	0	0
20	Striping Detail # 10 (Markers)	LF	0	0	0	0	0	0	0	0	0	0
21	Striping Detail # 22 (Thermo & Markers)	LF	0	0	0	0	0	0	0	0	0	0
22	Striping Detail # 27B (Thermo)	LF	0	680	0	0	0	0	0	0	0	0
23	Striping Detail 27B Modified 4'seg with 6' gap) thermo	LF	0	100	0	0	0	0	0	0	0	0
24	Striping Detail # 39 (Thermo)	LF	0	630	0	0	0	0	0	0	0	0
25	Striping Detail # 39A (Thermo)	LF	0	300	0	0	0	0	0	0	0	0
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	0	0	0	0	0	0	0	0	0	0
27	"STOP" Legend (Pre-formed Thermo)	EA	0	0	2	1	0	2	2	0	2	1
28	"SLOW" Legend (Pre-formed Thermo)	EA	0	2	0	0	0	0	0	0	0	0
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	0	2	0	0	0	0	0	0	0	0
30	"XING" Legend (Pre-formed Thermo)	EA	0	2	0	0	0	0	0	0	0	0
31	"25" Legend (Pre-formed Thermo)	EA	0	2	0	0	0	0	0	0	0	0
32	"YIELD" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
33	"BUMP" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
34	Green Bike Lane (Pre-formed Thermo)	SF	0	546	0	0	0	0	0	0	0	0
35	Bike Rider Symbol (Pre-formed white on green)	EA	0	4	0	0	0	0	0	0	0	0
36	Bike Rider Arrow (Pre-Formed white on green)	EA	0	4	0	0	0	0	0	0	0	0
37	Bike Detection Symbol (Pre-formed white on green)	EA	0	1	0	0	0	0	0	0	0	0
38	Arrow Type IV (Pre-formed Thermo)	EA	0	11	0	0	0	0	0	0	0	0
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	0	12	0	0	0	0	0	0	0	0
40	Replace Traffic Signal Loops	EA	0	0	0	0	0	0	0	0	0	0
41	Remove/Install Speed Bump (City detail 17-A)	EA	0	0	0	0	0	0	0	0	0	0
42	Remove/Install Speed Bump (Modified City detail 17-A 12' section)	EA	0	0	0	0	0	0	0	0	0	0
43	6" AC Dike	LF	0	0	0	0	0	0	0	0	0	0

2017 Pavement Maintenance Project												
Engineer's Estimate - \$3,560,000.00												
		AREA #	26	27	31	31	31	31	31	31	32	33
Estimated Quantities			OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY
BID ITEM NO.	BID ITEM	UNIT	Norwich (Amherst to Merritt)	Will Ct (Lazaneo to End)	Beaven (Stokes to Noel)	Clearcreek Ct (Phar Lap to End)	Clearwood Ct (Phar Lap to End)	Creekside Ct (Phar Lap to End)	Noel Ave (Beaven to Fitzgerald)	Oasis Ct (Alpine to End)	Alpine (Salem to Foothill)	Janice Ave (Mira Vista to Stevens Creek)
		AREA	38,256	8,293	9,994	13,475	7,691	7,587	34,727	7,085	56,230	32,172
1	Traffic Control	LS	---									
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	115	25	30	40	23	23	104	21	169	97
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	488	106	127	172	98	97	443	90	717	410
4	Pavement Fabric	SY	4,028	868	1,058	1,431	809	797	3,659	749	5,914	3,397
5	Keycut A	LF	2000	482	470	600	410	410	1800	340	3000	1600
6	keycut B	LF	100	60	40	60	60	60	50	50	270	230
7	Adjust Survey Monument Cover to Finish Grade	EA	0	2	1	2	1	1	3	1	7	10
8	Replace Monument Box	EA	0	0	0	0	0	0	0	0	0	0
9	Lower Manhole Covers Prior to Cold Planing	EA	0	0	0	0	0	0	0	0	0	3
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold	EA	0	0	0	0	0	0	0	0	0	2
11	Adjust Manhole Covers to Finish Grade	EA	3	1	2	2	1	1	6	1	5	8
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Gra	EA	0	0	0	0	0	0	0	0	0	5
13	Install Blue RPM's @ Fire Hydrant	EA	0	0	0	0	0	0	0	0	2	1
14	6" White Lines (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
15	12" White Hatch (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
16	12" White Crosswalk/Limit Line (Thermo)	LF	0	0	0	0	0	0	0	0	30	100
17	12" Yellow Crosswalk (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
18	24" White (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
19	24" Yellow (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
20	Striping Detail # 10 (Markers)	LF	0	0	0	0	0	0	0	0	0	0
21	Striping Detail # 22 (Thermo & Markers)	LF	0	0	0	0	0	0	0	0	0	0
22	Striping Detail # 27B (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
23	Striping Detail 27B Modified 4'seg with 6' gap) thermo	LF	0	0	0	0	0	0	0	0	0	0
24	Striping Detail # 39 (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
25	Striping Detail # 39A (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	0	0	0	0	0	0	0	0	0	0
27	"STOP" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	1	4
28	"SLOW" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
30	"XING" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
31	"25" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	1	1
32	"YIELD" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
33	"BUMP" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
34	Green Bike Lane (Pre-formed Thermo)	SF	0	0	0	0	0	0	0	0	0	0
35	Bike Rider Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
36	Bike Rider Arrow (Pre-Formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
37	Bike Detection Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
38	Arrow Type IV (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	0	0	0	0	0	0	0	0	0	0
40	Replace Traffic Signal Loops	EA	0	0	0	0	0	0	0	0	0	0
41	Remove/Install Speed Bump (City detail 17-A)	EA	0	0	0	0	0	0	0	0	0	0
42	Remove/Install Speed Bump (Modified City detail 17-A 12' section)	EA	0	0	0	0	0	0	0	0	0	0
43	6" AC Dike	LF	0	0	0	0	0	0	0	0	0	0

2017 Pavement Maintenance Project												
Engineer's Estimate - \$3,560,000.00												
		AREA #	33	33	36	36	37	37	37	38	38	38
Estimated Quantities			OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY	OVERLAY
BID ITEM NO.	BID ITEM	UNIT	Rancho PI (Rancho Ventura to End)	Rancho Ventura St (Foothill to Palo Vista)	Mc Klintock Ln (Voss to Woodridge)	Meadow PI (Voss to End)	Anthony PI (Salem to End)	Byerly Ct (Salem to End)	Silver Oak Way (Foothill to Lazy Oak Ct)	Madrone Ct (End to End)	Manzanita Ct (End to End)	Peralta Ct (Canyon Oak to End)
		AREA	6,832	26,530	11,516	9,050	14,111	6,642	9,600	19,104	26,373	8,638
1	Traffic Control	LS					---	---	---		---	---
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	20	80	35	27	42	20	29	57	79	26
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	87	338	147	115	180	85	122	244	336	110
4	Pavement Fabric	SY	719	2,798	1,196	952	1,473	687	1,023	1,998	2,717	899
5	Keycut A	LF	360	1352	750	480	850	460	390	1120	1920	550
6	keycut B	LF	70	140	80	45	45	50	120	80	80	40
7	Adjust Survey Monument Cover to Finish Grade	EA	1	4	0	1	6	3	0	7	8	1
8	Replace Monument Box	EA	0	0	0	0	0	0	0	0	0	0
9	Lower Manhole Covers Prior to Cold Planing	EA	0	0	0	0	1	0	0	0	0	0
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold	EA	0	0	0	0	0	0	0	0	0	0
11	Adjust Manhole Covers to Finish Grade	EA	1	0	1	1	3	0	0	5	6	1
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Gra	EA	0	0	0	0	2	0	0	0	0	0
13	Install Blue RPM's @ Fire Hydrant	EA	0	0	0	0	1	0	0	0	2	0
14	6" White Lines (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
15	12" White Hatch (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
16	12" White Crosswalk/Limit Line (Thermo)	LF	0	30	0	0	0	25	30	0	0	0
17	12" Yellow Crosswalk (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
18	24" White (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
19	24" Yellow (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
20	Striping Detail # 10 (Markers)	LF	0	0	0	0	0	0	0	0	0	0
21	Striping Detail # 22 (Thermo & Markers)	LF	0	0	0	0	0	0	0	0	0	0
22	Striping Detail # 27B (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
23	Striping Detail 27B Modified 4'seg with 6' gap) thermo	LF	0	0	0	0	0	0	0	0	0	0
24	Striping Detail # 39 (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
25	Striping Detail # 39A (Thermo)	LF	0	0	0	0	0	0	0	0	0	0
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	0	0	0	0	0	0	0	0	0	0
27	"STOP" Legend (Pre-formed Thermo)	EA	0	1	0	0	0	1	1	0	0	0
28	"SLOW" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
30	"XING" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
31	"25" Legend (Pre-formed Thermo)	EA	0	1	0	0	0	0	0	0	0	0
32	"YIELD" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
33	"BUMP" Legend (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
34	Green Bike Lane (Pre-formed Thermo)	SF	0	0	0	0	0	0	0	0	0	0
35	Bike Rider Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
36	Bike Rider Arrow (Pre-Formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
37	Bike Detection Symbol (Pre-formed white on green)	EA	0	0	0	0	0	0	0	0	0	0
38	Arrow Type IV (Pre-formed Thermo)	EA	0	0	0	0	0	0	0	0	0	0
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	0	0	0	0	0	0	0	0	0	0
40	Replace Traffic Signal Loops	EA	0	0	0	0	0	0	0	0	0	0
41	Remove/Install Speed Bump (City detail 17-A)	EA	0	0	0	0	0	0	0	0	0	0
42	Remove/Install Speed Bump (Modified City detail 17-A 12' section)	EA	0	0	0	0	0	0	0	0	0	0
43	6" AC Dike	LF	0	0	0	0	0	0	0	0	0	0

2017 Pavement Maintenance Project			
Engineer's Estimate - \$3,560,000.00			
		AREA #	
Estimated Quantities			
BID ITEM NO.	BID ITEM	UNIT	
		AREA	
1	Traffic Control	LS	1
2	Leveling Course -No. 4 Hot Mix Asphalt Type A	TN	5,075
3	Hot Mix Asphalt, 1/2" Maximum Type A	TN	21,568
4	Pavement Fabric	SY	177,673
5	Keycut A	LF	92,514
6	keycut B	LF	6,320
7	Adjust Survey Monument Cover to Finish Grade	EA	174
8	Replace Monument Box	EA	0
9	Lower Manhole Covers Prior to Cold Planing	EA	29
10	Lower Cleanout / Water / Gas Valve Cover Prior to Cold	EA	16
11	Adjust Manhole Covers to Finish Grade	EA	188
12	Adjust Cleanout / Water / Gas Valve Cover to Finish Gra	EA	31
13	Install Blue RPM's @ Fire Hydrant	EA	42
14	6" White Lines (Thermo)	LF	611
15	12" White Hatch (Thermo)	LF	0
16	12" White Crosswalk/Limit Line (Thermo)	LF	1,645
17	12" Yellow Crosswalk (Thermo)	LF	100
18	24" White (Thermo)	LF	0
19	24" Yellow (Thermo)	LF	1,530
20	Striping Detail # 10 (Markers)	LF	1,060
21	Striping Detail # 22 (Thermo & Markers)	LF	2,100
22	Striping Detail # 27B (Thermo)	LF	680
23	Striping Detail 27B Modified 4'seg with 6' gap) thermo	LF	100
24	Striping Detail # 39 (Thermo)	LF	630
25	Striping Detail # 39A (Thermo)	LF	300
26	"Ahead Legend" Yellow (Pre-formed thermo)	EA	1
27	"STOP" Legend (Pre-formed Thermo)	EA	37
28	"SLOW" Legend (Pre-formed Thermo)	EA	4
29	"SCHOOL" Legend (Pre-formed Thermo)	EA	4
30	"XING" Legned (Pre-formed Thermo)	EA	4
31	"25" Legend (Pre-formed Thermo)	EA	11
32	"YIELD" Legend (Pre-formed Thermo)	EA	0
33	"BUMP" Legend (Pre-formed Thermo)	EA	14
34	Green Bike Lane (Pre-formed Thermo)	SF	546
35	Bike Rider Symbol (Pre-formed white on green)	EA	4
36	Bike Rider Arrow (Pre-Formed white on green)	EA	4
37	Bike Detection Symbol (Pre-formed white on green)	EA	1
38	Arrow Type IV (Pre-formed Thermo)	EA	12
39	Sharrows (Pre-formed MUTCD figure 9C-9)	EA	12
40	Replace Traffic Signal Loops	EA	3
41	Remove/Install Speed Bump (City detail 17-A)	EA	2
42	Remove/Install Speed Bump (Modified City detail 17-A 12' section)	EA	6
43	6" AC Dike	LF	500